



SKF 22326 CCJA/W33VA406

Spherical roller bearing for vibratory applications, with relubrication features

Spherical roller bearings can accommodate heavy loads in both directions. They are self-aligning and accommodate misalignment and shaft deflections, with virtually no increase in friction or temperature. This bearing design offers excellent performance in many types of vibrating machinery. The design includes features to facilitate relubrication. The bearings can be used in a modular system, including housings, sleeves and nuts.

Technical specifications

General	
Bore type	Cylindrical
Dimensions	
Bore diameter	130 mm
Outside diameter	280 mm
Width	93 mm
Shoulder diameter of inner ring	164 mm
Shoulder/recess diameter of outer ring	233 mm
Width of lubrication groove	16.7 mm
Diameter of lubrication hole	9 mm
Chamfer dimension	4 mm
ISO tolerance class for dimensions	Normal, bore to P5 and outside diameter P6
Abutment dimensions	
Diameter of shaft abutment	147 mm
Diameter of housing abutment	263 mm
Radius of fillet	3 mm
Calculation data	
SKF performance class	SKF Explorer
Basic dynamic load rating	1176 kN
Basic static load rating	1320 kN
Fatigue load limit	114 kN
Reference speed	1800 r/min
Limiting speed	2400 r/min
Limiting value	0.35
Calculation factor	1.9
Calculation factor	2.9
Calculation factor	1.8
Permissible rotational acceleration for oil lubrication	853 m/s ²
Permissible linear acceleration for oil lubrication	196 m/s ²
Radial internal clearance	
Minimum initial clearance	190 µm
Maximum initial clearance	240 µm
Performance	
Basic dynamic load rating	1176 kN
Basic static load rating	1320 kN
Reference speed	1800 r/min
Limiting speed	2400 r/min
SKF performance class	SKF Explorer
Properties	
Number of rows	2
Locating feature, bearing outer ring	Without
Bore type	Cylindrical

Cage	Surface-hardened sheet metal
Radial internal clearance	C4
Tolerance class for dimensions	Normal, bore to P5 and outside diameter P6
Sealing	Without
Lubricant	None
Relubrication feature	With
Candidate for remanufacturing	Yes
Indicative carbon footprint for new product	99.5 kg CO ₂ e
Indicative carbon footprint for remanufactured product	34.8 kg CO ₂ e

Logistics	
Product net weight	27.6 kg
eClass code	23-05-09-11
UNSPSC code	31171510

SKF drawings

