



SKF SNL 507-606

Корпусная деталь / стопорная шайба SKF

Корпуса и стопорные шайбы — вспомогательные элементы для монтажа подшипников. Обеспечивают фиксацию и защиту от осевого смещения.

Характеристики

Размеры	
Diameter of bearing seat	72 mm
Tolerance class of bearing seat diameter	G7
Width of bearing seat	34 mm
Centre height of bearing seat	50 mm
Внутренний диаметр (d)	46.5 mm
Overall width	83 mm
Foot width	52 mm
Thread of relubrication holes	1/8-27 NPSF
Overall height	93 mm
Foot height	22 mm
Overall length	185 mm
Distance between attachment bolts	150 mm
Length of attachment bolt hole	20 mm
Width of attachment bolt hole	15 mm
Inside width between seal grooves	59 mm
Width of seal groove	5 mm
Distance to seal groove back face	8 mm
Width at bore diameter	11 mm
Diameter of seal groove	54.5 mm
Distance between dowel pins	172 mm
Axial offset of dowel pins	19 mm
Diameter of dowel pins	5 mm
Высота центра (пиллоу-блок)	50 mm
Расстояние между болтами	150 mm
Attachment bolt diameter	12 mm

Расчётные данные	
Breaking load at 0° load angle (if the housing is not supported over its entire base)	140 kN
Breaking load at 55° load angle	190 kN
Breaking load at 90° load angle	115 kN
Breaking load at 120° load angle	85 kN
Breaking load at 150° load angle	80 kN
Breaking load at 180° load angle	95 kN
Breaking load, axial	60 kN
Load to reach yield point at 120° load angle	150 kN
Load to reach yield point at 150° load angle	85 kN
Load to reach yield point at 180° load angle	75 kN

Materials	
Housing material	Чугун
Corrosion protection	Paint - in accordance with ISO 12944-2, corrosivity category C2

Информация по монтажу	
Recommended diameter of attachment bolts	12 mm
Recommended tightening torque for attachment bolts	80 N·m

Size of cap bolts	M10x50
Tightening torque for cap bolts	50 N·m
Initial grease fill, 20%	30 g
Initial grease fill, 40%	50 g

Included products	
Пресс-маслёнка	АН 1/8-27 PTF

Свойства	
Тип корпуса	Plummer/pillow block
Housing configuration	Two-piece
Способ монтажа	Through shaft/Shaft end
Число отверстий под болты	2
Материал корпуса	Чугун
Bearing housing seal type	Без
Housing lubrication feature/possibility	Пластичная (консистентная)

Логистика	
Масса нетто	2.4 kg
Код eClass	23-05-17-01
Код UNSPSC	31171519





