


SKF TWIM 15/230V

Инструмент SKF

Инструменты SKF для монтажа и демонтажа подшипников — ударные ключи, нагреватели, съёмники, гидравлические гайки. Обеспечивают безопасную и точную установку.



Характеристики

Размеры	
Dimensions (W x L x H)	450 x 500 x 100 mm

Характеристики	
Heating performance example (bearing, weight, temperature, time)	6320, 7.1 kg, 110 °C, 5 min 20 sec

Свойства	
Рекомендуемые применения	Fans and blowers;Compressors;Roller conveyors;Bearing houses;Gear boxes;Electrical motors;Pump installations;Engines
Тип	Induction heater, portable
Серия	TWIM 15
Heating method	Induction, medium frequency
Suitable for mounting	Да
Suitable for dismounting	Нет
Solid workpiece weight (max, mounting)	10 kg
Bearing weight (max)	20 kg
Workpiece bore diameter (mounting)	Array mm
Workpiece outer diameter	Array mm
Power consumption (max)	2300 W
Workpiece width (max)	85 mm
Voltage	200-240 V
Voltage frequency	50 / 60 Hz
Current (max)	10 A
Temperature measurement	Magnetic probe K-type
Number of temperature sensors	1
Demagnetisation after heating	Да
Error guiding codes	Да
Heating temperature (max)	200 °C
Thermal overload protection	Да
Display	7 segment LED display
Forced air cooling	Да
Power setting	10%;25%;50%;100%
Thermometer mode	Да
Time mode	Да
Remote control panel (wired)	Нет
Heating time control	Array s
Heating time steps	1 s
Heating temperature control	Array °C
Heating temperature steps	1 °C
Housing material	Glassfiber filled special PA
Цвет	Blue;Dark Grey
Content	Heater, Temperature probe (TWIM 15-3), 1 pair of heat resistant gloves (TMBA G11) and 1 shucko mains plug

Логистика	
Масса нетто	6.64 kg

Код eClass	23-05-19-01
Код UNSPSC	40101831