



SKF 16008

Deep groove ball bearing

Single row deep groove ball bearings are particularly versatile, have low friction and are optimized for low noise and low vibration, which enables high rotational speeds. They accommodate radial and axial loads in both directions, are easy to mount, and require less maintenance than many other bearing types.

Technical specifications

Dimensions	
Bore diameter	40 mm
Deviation limits of mid-range bore diameter	-0.01..0 mm
Outside diameter	68 mm
Deviation limits of mid-range outside diameter	-0.011..0 mm
Width	9 mm
Deviation limits of ring width	-0.06..0 mm
Shoulder diameter	49.4 mm
Shoulder diameter	58.6 mm
Chamfer dimension	0.3 mm
ISO tolerance class for dimensions	P6 and tighter width tolerance

Abutment dimensions	
Diameter of shaft abutment	42 mm
Diameter of housing abutment	66 mm
Radius of shaft or housing fillet	0.3 mm

Calculation data	
SKF performance class	SKF Explorer
Basic dynamic load rating	13.8 kN
Basic static load rating	10.2 kN
Fatigue load limit	0.44 kN
Reference speed	22000 r/min
Limiting speed	14000 r/min
Minimum load factor	0.02
Calculation factor	16

Tolerances of run-out	
Range of section height at inner ring of assembled bearing	10 µm
Range of section height at outer ring of assembled bearing	13 µm
ISO tolerance class for geometrical tolerances	P6

Performance	
Basic dynamic load rating	13.8 kN
Basic static load rating	10.2 kN
Reference speed	22000 r/min
Limiting speed	14000 r/min
SKF performance class	SKF Explorer

Properties	
Filling slots	Without
Number of rows	1
Locating feature, bearing outer ring	Without
Bore type	Cylindrical
Cage	Sheet metal
Matched arrangement	No
Radial internal clearance	CN
Material, bearing	Bearing steel

Coating	Without
Sealing	Without
Lubricant	None
Relubrication feature	Without
Indicative carbon footprint for new product	0.45 kg CO ₂ e

Logistics	
Product net weight	0.125 kg
eClass code	23-05-08-01
UNSPSC code	31171504

SKF drawings