



SKF 1215 K

Self-aligning ball bearing with tapered bore

Self-aligning ball bearings, with a tapered bore, have two rows of balls, a common sphered raceway in the outer ring and two deep uninterrupted raceway grooves in the inner ring. They are insensitive to angular misalignment of the shaft relative to the housing, which can be caused, for example, by shaft deflection. The tapered bore facilitates ease of mounting via adapter sleeves or withdrawal sleeves.

Technical specifications

Bore type	Tapered 1:12
Dimensions	
Bore diameter	75 mm
Outside diameter	130 mm
Width	25 mm
Shoulder diameter inner ring	93.05 mm
Shoulder diameter outer ring	114.2 mm
Chamfer dimension	1.5 mm
Abutment dimensions	
Abutment diameter housing	121 mm
Fillet radius	1.5 mm
Calculation data	
Basic dynamic load rating	39 kN
Basic static load rating	15.6 kN
Fatigue load limit	0.8 kN
Reference speed	10000 r/min
Limiting speed	6700 r/min
Permissible angular misalignment	2.5 °
Calculation factor	0.04
Limiting value	0.18
Calculation factor	3.6
Calculation factor	3.5
Calculation factor	5.4
Performance	
Basic dynamic load rating	39 kN
Basic static load rating	15.6 kN
Reference speed	10000 r/min
Limiting speed	6700 r/min
Properties	
Retaining feature, inner ring	None
Locating feature, bearing outer ring	Without
Number of rows	2
Bore type	Tapered 1:12
Cage	Sheet metal
Radial internal clearance	CN
Tolerance class	Normal
Material, bearing	Bearing steel
Coating	Without
Sealing	Without
Lubricant	None
Relubrication feature	Without
Indicative carbon footprint for new product	4.7 kg CO ₂

Logistics	
Product net weight	1.31 kg
eClass code	23-05-08-06
UNSPSC code	31171532

SKF drawings

