



SKF 65X85X10 HMSA10 V

Radial shaft seal with rubber outside diameter and single sealing lip, for oil or grease.

Radial shaft seals are used between rotating and stationary machine components, or between components in relative motion. HMSA10 seals are designed with a rubber outside diameter. They have a conventional sealing lip made of elastomer. A garter spring in the seal and a non-contacting auxiliary lip optimize the sealing against the shaft also in polluted environment.

Technical specifications

General	
Type of outside diameter	Rubber metal reinforced
Lip material	Fluoro rubber (FKM)
Seal design	HMSA10
Compliance with standard	ISO 6194; DIN 3760

Dimensions	
Shaft diameter	65 mm
Housing bore diameter	85 mm
Seal width	10 mm

Application and operating conditions	
Operating temperature	-25 °C
Operating temperature	200 °C
Operating temperature, short periods	200 °C
Circumferential speed	28.1 m/s
Rotational speed	8280 r/min
Pressure differential	0.05 N/mm ²

Associated products	
SKF Speedi-Sleeve	99254

Performance	
Limiting speed	8280 r/min
Maximum operating temperature	200 °C
Minimum operating temperature	-25 °C
Permissible circumferential speed	28.1 m/s
Rotational speed	8280 r/min

Properties	
Design	HMSA10
Auxiliary lip	Yes
Sealing lip material	Fluoro rubber (FKM)
Type of outside diameter	Rubber metal reinforced
Unit system	Metric

Logistics	
Product net weight	0.043 kg
eClass code	23-07-08-01
UNSPSC code	31181602

SKF drawings

