

SKF TKBA 11

Basic belt alignment, pulley side, red laser, 1 laser unit

The belt alignment tool has two main components; a laser-emitting unit and three passive targets. Each is attached quickly and easily – using a powerful magnet – to the inside or outside face of a belt pulley or chain sprocket. The tool can be applied to most machines that use V belts, banded belts and ribbed belts – as well as those with chain sprockets.

Technical specifications

Dimensions	
Transmitter dimensions (l x h x w)	98 x 97 x 52 mm
Target dimensions (l x h x w)	25 x 40 x 25 mm
Case dimensions (l x h x w)	260 x 85 x 180 mm
Performance	
Measurement distance	Array mm
Properties	
Recommended applications	Most machines using V belts, banded belts, ribbed belts, most other belts;Chain sprockets
Mounting	Magnetic, side mounted
Laser type	Visible red line laser
Laser wavelength	635 nm
Laser power max	1 mW
Laser line length (at 2 m)	2.4 m
Measurement accuracy angular (at 2 m)	0.02 °
Measurement accuracy offset	0.5 mm
Transmitter weight	0.25 kg
Target type	Set of 3 Passive targets
Target weight	0.035 kg
Housing material	PC/ABS blend, overmoulded with TPU rubber
Colour	Blue;Dark Grey
Battery	3x AAA (Alkaline (incl.) or Rechargeable)
Battery life	32 h
Degree of protection (IP)	IP 40
Operating temperature range	Array °C
Recommended storage temperature	Array °C
Relative humidity	10 to 90%, non-condensing
Content	1x TKBA 11 transmitter unit;3x passive targets;3x AAA batteries;1x printed instructions for use;1x Carrying case (size A)
Logistics	
Product net weight	0.763 kg
eClass code	23-05-19-01
UNSPSC code	41112202