



SKF FYJ 100 TF

Square flanged ball bearing unit with set screw locking, cast iron housing, JIS

These square flanged ball bearing units are compliant with Japanese Industrial Standards (JIS). They consist of an insert bearing, with an extended inner ring and set screw locking, and are suitable for applications where the direction of rotation is constant or alternating. The bearing is mounted in a cast iron housing, which can be bolted to a machine wall or frame. Ball bearing units can accommodate moderate initial misalignment, but normally do not permit axial displacement.

Technical specifications

General	
Compliance with standard	JIS
Purpose specific	For material handling applications
Material, housing	Cast iron
Sealing, bearing	Seal and flinger on both sides
Sealing type, bearing	Contact, standard
Sealing, unit	Without
Coating	Without

Dimensions	
Bore diameter	100 mm
Outer diameter of inner ring	124.8 mm
Width of housing	70 mm
Flange width	25 mm
Depth of centring recess	3.2 mm
Width of inner ring	98.4 mm
Overall bearing width	98.4 mm
Distance from locking device side face to thread centre	18 mm
Top external diameter	207 mm
Base external diameter	221 mm
Diameter of housing centering recess	215.9 mm
Centre distance between bolt holes	210 mm
Overall length	265 mm
Diameter of attachment bolt hole	27 mm
Distance from locking device side face to raceway centre	63.4 mm
Overall width	107.5 mm
Housing thread for grease fitting	1/4-28 UNF
Axial position of the housing thread	43 mm
Diameter of head sphere of grease fitting	6.5 mm
Hexagonal key size for the grease fitting	7 mm
Thread of grease fitting	1/4-28 SAE-LT
Distance of dowel pins	233 mm
Axial offset of dowel pins	55 mm
Recommended diameter for dowel pins	4 mm
Attachment bolt diameter	24 mm
Shaft diameter	100 mm
Housing overall width	70 mm
Width, total	107.5 mm
Bearing width, total	98.4 mm

Calculation data	
Basic dynamic load rating	124 kN
Basic static load rating	93 kN
Fatigue load limit	3.35 kN
Limiting speed	1900 r/min
	Limiting speed with shaft tolerance h6

Mounting information	

Set screw	M12x1.5
Hexagonal key size for set screw	6 mm
Recommended tightening torque for set screw	28.5 N·m
Recommended diameter for attachment bolts, mm	24 mm
Recommended diameter for attachment bolts, inch	0.9375 in

Performance	
Basic dynamic load rating	124 kN
Basic static load rating	93 kN
Limiting speed	1900 r/min
Note	Limiting speed with shaft tolerance h6

Properties	
Housing type	Flanged
Flanged housing type	Square
Number of bolt holes for fasteners	4
Fastening bolt hole type	Plain
Retaining feature, inner ring	Set screws
Bore type	Cylindrical
Rubber seating ring	Without
Material, housing	Cast iron
Material, bearing	Bearing steel
Coating	Without
Sealing, bearing	Seal and flinger on both sides
Sealing type	Contact, standard
Sealing, unit	Without
Lubricant	Grease
Relubrication hole	With
Grease fitting	With

Logistics	
Product net weight	14.6 kg
eClass code	23-05-16-02
UNSPSC code	31171536

SKF drawings

