


SKF SYJ 30 TF



Pillow block ball bearing unit with extended inner ring and set screw locking, cast iron housing

Pillow (plummer) block ball bearing units consist of an insert bearing mounted in a cast iron housing that can be bolted to a support surface. This variant is suitable for applications with both constant and alternating directions of rotation. It has an inner ring extended on both sides and is locked onto the shaft by tightening a set screw on the inner ring, making it easy to mount.

Technical specifications

General	
Compliance with standard	JIS
Purpose specific	For material handling applications
Material, housing	Cast iron
Sealing, bearing	Seal and flinger on both sides
Sealing type, bearing	Contact, standard
Sealing, unit	Without
Coating	Without

Dimensions	
Bore diameter	30 mm
Shoulder diameter of inner ring	39.7 mm
Base width	42 mm
Top width	27 mm
Width of inner ring	38.1 mm
Distance from locking device side face to thread centre	5 mm
Height of spherical seat centre	42.9 mm
Foot height	16 mm
Overall height	82 mm
Distance between attachment bolts	118 mm
Maximum distance between attachment bolts	125 mm
Minimum distance between attachment bolts	111 mm
Overall length	165 mm
Diameter of attachment bolt hole	17 mm
Length of attachment bolt hole	24 mm
Distance from locking device side face to raceway centre	22.2 mm
Housing thread for the grease fitting	1/4-28 UNF
Axial position of the housing thread	3 mm
Angular position of the housing thread	45 °
Diameter of head sphere of grease fitting	6.5 mm
Hexagonal key size for the grease fitting	7 mm
Thread of grease fitting	1/4-28 SAE-LT
Distance of dowel pins	155 mm
Axial offset of dowel pins	15 mm
Recommended diameter for dowel pins	4 mm
Attachment bolt diameter	14 mm
Shaft diameter	30 mm
Centre height (pillow block)	42.9 mm
Housing overall width	42 mm
Centre distance between bolt holes	118 mm
Bearing width, total	38.1 mm

Calculation data	
Basic dynamic load rating	19.5 kN
Basic static load rating	11.2 kN
Fatigue load limit	0.475 kN
Limiting speed	6300 r/min
	Limiting speed with shaft tolerance h6

Mounting information	
Set screw	M6x0.75
Hexagonal key size for set screw	3 mm
Recommended tightening torque for set screw	4 N·m
Recommended diameter for attachment bolts, mm	14 mm
Recommended diameter for attachment bolts, inch	0.5625 in

Performance	
Basic dynamic load rating	19.5 kN
Basic static load rating	11.2 kN
Limiting speed	6300 r/min
Note	Limiting speed with shaft tolerance h6

Properties	
Housing type	Pillow block, normal base
Number of bolt holes for fasteners	2
Fastening bolt hole type	Plain
Retaining feature, inner ring	Set screws
Bore type	Cylindrical
Rubber seating ring	Without
Material, housing	Cast iron
Material, bearing	Bearing steel
Coating	Without
Sealing, bearing	Seal and flinger on both sides
Sealing type	Contact, standard
Sealing, unit	Without
Lubricant	Grease
Relubrication hole	With
Grease fitting	With

Logistics	
Product net weight	1.11 kg
eClass code	23-05-16-02
UNSPSC code	31171536

SKF drawings